

CLAIM AMENDMENTS

1-63. (Cancelled)

64. (Withdrawn) A catheter assembly for the controlled ablation of tissue using radio frequency (RF) energy, comprising:

a first tubular end attachable to a source of electrolyte fluid for delivering fluid through the lumen;

an electrode on the distal end of the first tubular member, the electrode being connectable to a source of RF energy; and

a second tubular member having a proximal end, a distal end sized for insertion into a patient's body, and a lumen extending between the proximal and distal ends within which the first tubular member is received such that the distal end of the second tubular member is offset distally from the distal end of the first tubular member, thereby disposing the electrode within the lumen of the second tubular member;

whereby RF energy may be transferred from the electrode to tissue beyond the distal end of the second tubular member via electrolyte fluid delivered through the lumen of the first tubular member.

65. (Withdrawn) The catheter assembly of claim 64, wherein the first tubular member is slidably disposed within the lumen of the second tubular member such that the first tubular member provides a fluid-tight seal preventing fluid flow between the first and second tubular members.

66. (Withdrawn) The catheter assembly of claim 64, wherein the first tubular member is substantially smaller than the lumen of the second tubular member, thereby defining an annular lumen therebetween through which fluid may flow.

67. (Withdrawn) The catheter assembly of claim 64, wherein a distance between the distal end of the second tubular member and the distal end of the first tubular member is between about 0.08 inches and about 0.05 inches when the first tubular member is fully inserted within the second tubular member.

68. (Withdrawn) The catheter assembly of claim 64, further comprising a conductor extending proximally from the electrode through the first tubular member for coupling the electrode to a source of RF energy.

69. (Withdrawn) The catheter assembly of claim 68, further comprising a wire lumen extending through the first tubular member, the conductor extending through the wire lumen such that the wire lumen electrically insulates the conductor from the electrolyte fluid.

70. (Currently Amended) An apparatus for ablating body tissue using radio frequency (RF) energy, comprising:

a catheter having a proximal portion attachable to a source of electrolyte fluid, a distal portion sized for insertion into a patient's body, and a lumen for delivering fluid from the proximal portion to the distal portion;

an expandable member disposed on the distal portion of the catheter and comprising a substantially planar distal end, the expandable member defining an interior region in communication with the lumen; and

an RF electrode on the distal portion and communicating with the lumen, the electrode configured for coupling to a source of RF energy, whereby RF energy may be transferred from the electrode to selected tissue areas in a patient's body via electrolyte fluid delivered through the lumen and into the interior region of the expandable member, the electrode extends from the distal portion of the catheter, the electrode comprising an interior communicating with the lumen.

71. (Canceled).

72. (Previously Added) The apparatus of claim 70, wherein the expandable member is attached to the distal portion such that a substantially smooth outer surface profile is presented by the distal portion.

73. (Previously Added) The apparatus of claim 70, wherein the distal portion extends into an interior space of the expandable member.

74. (Previously Added) The apparatus of claim 70, wherein the expandable member defines an interior space in communication with the lumen and wherein the electrode is disposed within the interior space.

75. (Previously Added) The apparatus of claim 74, wherein the electrode comprises a plurality of apertures, the apertures allowing electrolyte fluid to pass therethrough into the interior space.

76. (Previously Added) The apparatus of claim 70, wherein the expandable member further comprises a plurality of perforations to allow flow of electrolyte fluid from an interior space of the expandable member to the selected tissue areas beyond the expandable member.

77. (Withdrawn) The apparatus of claim 70, wherein the electrode is disposed within the lumen.

78-81. (Canceled)

82. (Previously Amended) An apparatus for ablating body tissue using radio frequency (RF) energy, comprising:

- a source of RF energy;
- a catheter having a proximal portion attachable to a source of electrolyte fluid, a distal portion sized for insertion into a patient's body, and a lumen for delivering fluid from the proximal portion to the distal portion;
- a porous member attached to the distal portion of the catheter, the porous member defining an interior region in communication with the lumen, the interior region capable of receiving electrolyte fluid delivered from the proximal portion of the catheter; and
- an electrode disposed in the interior region and coupled to the source of RF energy the electrode extends from the distal portion of the catheter.

83. (Canceled)

84. (Previously Presented) The apparatus of claim 82, wherein the porous member has a substantially planar distal end.

85. (Previously Presented) The apparatus of claim 70, wherein the catheter is flexible.

86. (Previously Presented) The method of claim 79, wherein the catheter is flexible.

87. (Previously Presented) The method of claim 82, wherein the catheter is flexible.